



## VELOMATIC ATF

**AUTOMATIC AND POWER SHIFT  
TRANSMISSION FLUID  
DEXRON-III**

LAUGFS VELOMATIC ATF, a new generation petroleum based product for automatic and power shift transmissions. The highest level product of ATF are suitable for use both GM Dexron III with 6297-M and Ford Mercon specification M2C185A. In addition, it also meets Allison C-4 fluid and is qualified as a PSF specification. LAUGFS VELOMATIC ATF provide superior wear protection for all passenger car and light trucks requiring the use of TASA, Dexron II D, Dexron II E or Dexron III G/H/M ATFs.

### PRODUCT FEATURES & BENEFITS

- Automatic Transmission Fluids are recommended for mobile equipment used by utility companies, which require electrical insulating properties for hydraulic oils.
- Passenger cars and light truck automatic transmissions, on-highway heavy duty transmission applications requiring Dexron III performance level
- Power steering system where the manufacture recommends a Dexron III fluid Off-Highway power transmission requiring Allison C-4
- Mobile, industrial and marine hydraulic systems (where a Dexron III type is required)
- Any other transmission system for which Dexron, Dexron II or Dexron III oil is recommended

### APPLICATIONS

- Provides prompt and reliable lubrication in both high and low temperature operating condition
- Enhanced protection against wear to prolong transmission life
- Improved cleanliness of transmission system
- Exceptional thermal and oxidation stability
- Proven compatibility with elastomers



### PERFORMANCE CHARACTERISTICS

<b>Product Name</b>	<b>LAUGFS VELOMATIC ATF</b>
<b>Product Category</b>	<b>Automatic and Power shift transmission</b>
<b>SAE Grade</b>	<b>SAE 10W</b>
<b>OEM recommendations and Performance meets</b>	<b>DEXRON III H, DEXRON III M, DEXRON III G, DEXRON II E, DEXRON II D, Ford ESP-M2C138-CJ, Ford ESP-M2C166-H, MERCON-M2C185A, ALLISON C-4 ALLISON C-3, PSF ( Power steering Fluid), TASA, Cat TO-2</b>



### KEY PROPERTIES

Parameter	Test Method	Unit	Typical value
Appearance	Visual	-	RED
Density @ Room temperature	ASTM D4052	g/mL	0.84
Kinematic Viscosity at 40° C	ASTM D445	cSt	33.5 - 36.5
Kinematic Viscosity at 100° C	ASTM D445	cSt	7.0 - 8.0
Viscosity Index	ASTM D2270	-	175
Flash Point(COC),	ASTM D92	°C	195
Pour Point,	ASTM D97	°C	(-45)

\* This is a technical Specification for LAUGFS Product according to the current additive package. It may have minor deviations on basis of supply.

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.