## **Transmission Fluid**





**LAUGFS GEARON X,** SAE 80W 90, API GL-5 high performance, gear lubricants are formulated from base oils and specially selected additive system for use in automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected.

## **PRODUCT FEATURES & BENEFITS**

- · Long gear life
- Exceptional thermal stability and resistance to high oxidation
- · Excellent rust and corrosion protection
- · Excellent Foam inhibition
- · Long Lubricant Life
- · Effective low temperature lubrication
- · Seal protection

## **APPLICATIONS**

 Spiral bevel and Hypoid differentials, power dividers, and oil lubricated steering axle wheel bearing requiring API GL-5/ GL-4 performance requirement



SOCIETY OF AUTOMOTIVE ENGINEERS VISCOSITY CLASSIFICATION

**SAE 80W-90** 

AMERICAN PETROLEUM INSTITUTE PERFORMANCE CLASSIFICATION

API GL-5



## **KEY PROPERTIES**

Parameter	Typical value SAE-80W 90	Method
SAE Grade	Clear & Bright	
Viscosity		ASTM D445
cSt @ 40°C	155	
cSt @ 100°C	16.50 - 17.50	
Viscosity index	106	ASTM D2270
Pour Point, °C	-33	ASTM D97
Flash Point, °C	210	ASTM D92
Density @ 15°C kg/l	0.89	ASTM D4052

Note: This document does not constitute specifications of the product  $% \left( 1\right) =\left( 1\right) \left( 1$ 

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.