

## Motorcycle Oil Category



# REVTRON 4T

SAE 20W-40

Four-Stroke Motorcycle Engine Oil

API SL  
JASO MA2

REVTRON 4T, SAE 20W-40 is a motorcycle oil is exclusively designed to meet and exceed the lubrication needs of the latest four stroke engine designs.

### PRODUCT FEATURES & BENEFITS

- Smooth clutch operation
- Ensure maximum engine performance
- Easy starting and riding even at high temperature
- Maximize engine and gearbox durability

### APPLICATIONS

- New generation four stroke engines of Bajaj, TVS, Yamaha, Suzuki, Hero and Honda which require SAE 20W-40 viscosity oils.



### PERFORMANCE CHARACTERISTICS

AMERICAN PETROLEUM INSTITUTE CLASSIFICATION

API SL

JAPANESE AUTOMOTIVE STANDARD ORGANIZATION PERFORMANCE CLASSIFICATION

JASO MA2



### KEY PROPERTIES

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	6.0 - 6.5	ASTM D1500
Kinematic Viscosity at 40°C, min, cSt	110	ASTM D445
at 100°C, cSt	13.50 - 14.50	
Viscosity index	125	ASTM D2270
Flash point, min °C	224	ASTM D92
Total base number, min mgKOH/g	5.70	ASTM D2896

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.