

Motorcycle Oil Category



REVTRON 4T

SAE 20W-50

Four-Stroke Motorcycle Engine Oil

**API SL
JASO MA2**

REVTRON 4T, SAE 20W-50 is a motorcycle oil is exclusively designed to meet and exceed the lubrication needs of the latest four stroke engine designs.

PRODUCT FEATURES & BENEFITS

- Smooth clutch operation
- Ensure maximum engine performance
- Easy starting and riding even at high temperature
- Maximize engine and gearbox durability

APPLICATIONS

- New generation four stroke engines with a capacity of 150cc or more where SAE 20W-50, API SL and JASO MA2 specifications are recommended.



PERFORMANCE CHARACTERISTICS

AMERICAN PETROLEUM INSTITUTE CLASSIFICATION

API SL

JAPANESE AUTOMOTIVE STANDARD ORGANIZATION PERFORMANCE CLASSIFICATION

JASO MA2



KEY PROPERTIES

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	6.0 - 6.5	ASTM D1500
Kinematic Viscosity at 40°C, min, cSt	145	ASTM D445
at 100°C, cSt	17.50 - 18.50	
Viscosity index	135	ASTM D2270
Flash point, min °C	228	ASTM D92
Total base number, min mgKOH/g	5.75	ASTM D2896

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.