



# SUPERTECH POWER P SAE 15W-40

Multigrade  
API SL



SUPERTECH POWER, 15W-40 is a multigrade petrol engine oil designed to lubricate a wide range of gasoline engines requiring API SL performance and SAE 15W-40 viscosity classification

### PRODUCT FEATURES & BENEFITS

- Faster cold weather start up and outstanding performance at high temperature operation.
- Increased engine durability.
- Minimize Operating cost.
- Protection from deposits.
- Extend drain Intervals

### APPLICATIONS

- For 2004 Year and older Gasoline engines where the manufacturer recommends require SAE 15W 40. and API SL or below (API SJ) Engine oil specifications
- Naturally aspirated gasoline engines in passenger cars
- Sport utility vehicles, Light duty gasoline truck engines, Vans



### PERFORMANCE CHARACTERISTICS

SOCIETY OF AUTOMOTIVE ENGINEERS  
VISCOSITY CLASSIFICATION

**SAE 15W-40**

AMERICAN PETROLEUM INSTITUTE  
PERFORMANCE CLASSIFICATION

**API SL**



### KEY PROPERTIES

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	2.5-3.0	ASTM D1500
Kinematic Viscosity at 40°C, min, cSt	105	ASTM D445
at 100°C, cSt	13.50-14.50	
Viscosity index, min	120	ASTM D2270
Flash point, min °C	200	ASTM D92
Total base number, min mgKOH/g	5.50	ASTM D2896

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.