# **Petrol Category**





**SUPREME PETRA GOLD,** SAE 5W-40, is a Fully Synthetic Hybrid oil that delivers the latest technology to maximize the protection for the newest engines fueled by gasoline. It meets the highest API SN performance and exceeds the most demanding requirements in relation to modern engine emission control systems.

### **PRODUCT FEATURES & BENEFITS**

- Reduces maintenance cost
- Protect engines from wear
- High thermal stability and oxidation stability
- Maximum durability

# **APPLICATIONS**

- Naturally aspirated and turbocharged petrol engines in passenger cars.
- Low emission passenger cars and light duty vehicle engines fitted with latest catalytic converters.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

#### PERFORMANCE CHARACTERISTICS

SOCIETY OF AUTOMOTIVE ENGINEERS VISCOSITY CLASSIFICATION

#### **SAE 5W-40**

AMERICAN PETROLEUM INSTITUTE PERFORMANCE CLASSIFICATION

**API SN** 

# **KEY PROPERTIES**

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	2.5-3.0	ASTM D1500
Kinematic Viscosity at 40°C cSt at 100°C cSt	95.0 13.0-15.0	ASTM D445
Viscosity index, min	150	ASTM D2270
Flash point, min °C	230	ASTM D92
Pour Point °C	Max-33	ASTM D97
Total base number, min mgKOH/g	7.0	ASTM D2896

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.