

SUPREME PETRA, SAE 15W-40 is a high quality engine oil for use in modern petrol passenger car and light-duty commercial vehicle engines where API SN, SM, SL are required. Supreme Petra Multigrade will maintain engine cleanliness and prolong engine life.

PRODUCT FEATURES & BENEFITS

- · Protects engines from wear
- · Preserves power and performance
- · Protection against in-service oil degradation



SOCIETY OF AUTOMOTIVE ENGINEERS VISCOSITY CLASSIFICATION

SAE 15W-40

AMERICAN PETROLEUM INSTITUTE PERFORMANCE CLASSIFICATION

API SN

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles.
- Power equipment where the manufacturer recommends conventional passenger car motor oils.



Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	2.5-3.0	ASTM D1500
Kinematic Viscosity at 40°C, min, cSt at 100°C, cSt	110 14.0-16.0	ASTM D445
Viscosity index, min	120	ASTM D2270
Flash point, min °C	200	ASTM D92
Total base number, min mgKOH/g	6.6	ASTM D2896

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.